

Practical Products Co. Woodworking, Laminate, Solid Surface, & Flooring Hand & Power Tools



J-ROLLER Handiest roller of all. The 3" rubber roller is soft enough to avoid marring but firm enough to smooth out all covering materials, and is conductive enough to prevent static build up. Up to 50 lb per square inch can be applied to assure thorough bonding of the adhesive layer. Since there are no axle protrusions on the open end, you can roll close to uprights without danger of marring. Light-weight with Comfort Grip handle, it is easy to use and to carry. [Cat. No. JR-78C](#), Length 13", Wt 10 oz, 24/ctn



CURVED FRAME J-ROLLER This heftier version J-Roller is 14 1/2" long. The curved steel frame provides left-hand clearance and permits the application of greater pressure which water-based contact adhesives usually require. Two heavy non-slip vinyl hand grips provide firm control. [Cat. No. JR-300](#), Length 15", Wt 1.5 lb, 12/ctn



EXTENSION ROLLER Three 2 1/4" resilient rollers let you cover a lot of territory in a hurry, be it decorative laminate, vinyl, or other adhesive-applied coverings. A favorite for decorative laminates, carpet, floor tile, and other resilient coverings. With the preferred loop handle grip at the roller section, heavy pressure can be applied right where it is needed - at the rollers. The twist-lock handle quickly adjusts from 18" to 27". [Cat. No. ER-333](#), Length 18", Wt 3 lb [Cat. No. ER-333RP](#), Replacement 3-Roller Set with Axle



SEAM ROLLERS These steel rollers apply leveling pressure to seams in decorative laminates, resilient flooring, and carpet so that the edges are pressed evenly and firmly in place. This provides the best seam appearance and assures bonding to prevent future lifting of edges. Also can be used to roll out blisters or air pockets. They have 9" hardwood handles, except SE-348S that has a 6" handle. The bearing-mounted rollers are plated for stain and rust resistance and to prevent marring of surfaces. Open ended for close areas.

- [Cat. No. SE-348](#), Both Edges Square, Length 12", Wt 2 1/4 lb
- [Cat. No. SE-349R](#), One Round Edge, Length 12", Wt 2 1/4 lb
- [Cat. No. SE-348S](#), Both Edges Square, Length 9", Wt 2 lb

SQUEEZE ROLLER This lever action roller puts pressure on laminate edges to seal them down tight to the substrate. Very useful for correcting the occasional edge-lift problem. The tip roller rides on the underside and the mid roller rides on the upper side to put handle pressure on the edge. The rollers are non-marring firm plastic. [Cat. No. SR-79](#), Length 12", Wt 10 oz



The **ACCURATE SCRIBE** is an indispensable tool for installing countertops, cabinets, tile, and floor coverings. Set spacing to equal widest gap between item and the irregular surface. Slide the Accurate Scribe along the irregular surface so that it follows the contour while the pencil marks along the item being installed. Trim to the pencil line to get a perfect fit with a minimum of material removal. Simple, effective. Blister packed on a display card.

[Cat. No. AS-1](#), Length 4 1/2", Wt 4 oz

STEEL TAPE RULES A key element for every professional is a high quality, easy-to-use, accurate measuring tape. These **STARRETT®** brand tape rules are highest quality with a chrome case and have a professional look and feel. Check this long list of features:




- *Very Lightweight
- *Smooth Easy-Out Action
- *Thumb-Action Lock
- *Power Return
- *Belt Clip (Removable)
- *Long Wearing & Easy to Read Black on Yellow Tape
- *Calibrated in 1/32nds for First 12", 1/16ths Thereafter
- *Metric/English Calibrated in Millimeters and Inches
- *Reinforced Slip Tip for Inside/Outside Accuracy & Long Wear
- *Wide Selection of Widths & Lengths

<u>Cat. No.</u>	<u>Width x Length</u>	<u>Calibrations</u>	<u>Weight</u>
C12-12	1/2" x 12'	Inches/Feet	4 oz
C34-16	3/4" x 16'	Inches/Feet	7 oz
C34-5ME12	3/4" x 5m(16')	Millimeters/Inches	7 oz
C1-25	1" x 25'	Inches/Feet	15 oz
C1-8ME12	1" x 8m(26')	Millimeters/Inches	16 oz

REPLACEMENT TAPES Keep one on hand to avoid work interruption. They are reverse wound in a dispensing box for easy insertion. [Cat. No. SK-25R](#), 3/4" x 25' [Cat. No. SK-125R](#), 1" x 25'

STIX TAPES Another neat item that has many uses - a flat steel (not plastic) adhesive-backed tape rule. Just press in place to mount it on a cutting table, workbench, drawing table, table saw, radial saw, or other location. It provides a "Quick Look" check on measurements without the necessity of handling a separate tape. A real timesaver, speeds production and helps prevent errors. **STARRETT** brand. Weight 2 oz each.



- | | | | |
|--|------------|--|------------|
| | Reads: | | Reads: |
| Cat. No. SM-66W , 3/4" x 6', | Left to Rt | Cat. No. SM-46WRL , 1/2" x 6', | Rt to Left |
| Cat. No. SM-412W , 1/2" x 12', | Left to Rt | Cat. No. SM-412WRL , 1/2" x 12', | Rt to Left |